



FRAME PART NO.	TRAVEL	Normal Duty Bearing Bore	WT.	B	C	D	E	F		G	H	J	K	M	S	T
								QTY.	DIA.							
WST-100-03	3	1/2" thru 1"	5.5	9	7 3/8	6 7/8	5 9/16	4	7/16	2 15/16	3/16	1 3/4	1 1/16	3 1/16	5/8	1
WST-100-06	6		7.0	12		4 15/16		6								
WST-100-09	9		8.5	15		6 7/16		6								
WST-100-12	12		10.0	18		7 15/16		6								
WST-150-06	6	1-1/16" thru 1-7/16"	9.0	12 1/8	7 1/16	9 7/16	6 1/16	4	7/16	3 11/16	3/16	2	1 1/4	3 9/16	3/4	1
WST-150-09	9		10.5	15 1/8		6 7/32		6								
WST-150-12	12		12.0	18 1/8		7 23/32		6								
WST-150-18	18		15.5	24 1/8		10 23/32		6								
WST-200-06	6	1-1/2" thru 2"	14.0	13 3/4	8 13/16	11 1/2	7 5/16	4	1/2	4 5/16	3/16	2 1/2	1 7/16	4 1/16	1	1 1/8
WST-200-09	9		16.5	16 3/4		7 1/4		6								
WST-200-12	12		19.0	19 3/4		8 3/4		6								
WST-200-18	18		24.5	25 3/4		11 3/8		6								
WST-250-06	6	2" thru 2-7/16"	20.0	14 3/4	10 1/2	6 1/4	8 5/8	4	9/16	5 11/16	3/16	2 1/2	1 1/2	5 3/16	1 1/4	1 1/8
WST-250-09	9		23.5	17 3/4		9 1/4		4								
WST-250-12	12		27.0	20 3/4		12 1/4		6								
WST-250-18	18		34.0	23 3/4		18 1/4		6								
WST-250-24	24		41.0	32 3/4		24 1/4		6								
WST-300-09	9	2-1/2" thru 2-15/16"	36.0	21 1/4	12 7/8	7 1/4	10 1/4	4	5/8	6 1/2	1/4	3	2	6	1 1/2	2 1/2
WST-300-12	12		41.0	24 1/4		10 1/4		6								
WST-300-18	18		51.0	30 1/4		13 1/4		6								
WST-300-24	24		61.0	36 1/4		16 1/4		6								
WST-300-30	30		71.0	42 1/4		19 1/4		6								

NOTES:

- DESIGNED FOR USE WITH NORMAL DUTY BEARING (BEARING IS REQUIRED & SOLD SEPARATELY).
- CAN BE MODIFIED TO ACCEPT MEDIUM DUTY BEARINGS. CONTACT DOUGLAS FOR PRICING & DELIVERY INFORMATION.
- 100% WELDED FRAME ALLOWS FOR EASY BEARING INSERTION AND REMOVAL.
- ALL UNITS SUPPLIED WITH ACME™ THREADED ROD AND HEX NUTS.

All dimensions and specifications subject to change without notice.
 Certified dimensions and specifications of ordered material available on request.
 Copyright © 2015, Douglas Manufacturing Co., Inc. All rights reserved.